

DECLARATION OF PERFORMANCE
According to regulation (EU) No. 305/2011 of 9. March 2011
No. DoP-002/2013-07-01-EN



- 1 Unique identification code of the product-type:

Fibre-cement profiled sheets ESAL Profile 8 and ONDAPRESS 36 including fittings

- 2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ESAL Profile 8
CE 10 ESSI NT V8 SIST EN 494 B1X YY DDD

ONDAPRESS 36
CE 10 ESSI NT OP36 SIST EN 494 B1X YY DDD
(YY DDD = Year and day of production)

- 3 Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Profiled sheets and fittings for roof covering and facade cladding

- 4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ESAL d.o.o., Anhovo 9, SI-5210 Deskle
Tel. +386 5 392 15 72, Fax +386 5 392 16 57, www.esal.si

- 5 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

- 6 System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

- 7 In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Reaction to fire test:

Slovenian national Building and Civil Engineering Institute (ZAG),
Dimičeva 12, SI-1000 Ljubljana
Notified Body No. 1404

Reaction to fire Classification report No. P 582/04-530-5

- 8 In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable



9 Declared performance

Essential characteristics	Performance	Harmonised technical specification
Mechanical resistance	Category and class B1X	EN 494:2012
Impact resistance	NPD	
External fire performance	B _{roof} (Deemed to satisfy)	
Reaction to fire ^a	A2-s1,d0	
Water impermeability	Pass	
Dimensions and tolerances ^a	Pass	
Release of dangerous substances ^a	NPD	
Durability against: - warm water - soak-dry - freeze-thaw - heat-rain	Pass Pass Pass Pass	

^a Characteristics which apply to fittings. All characteristics apply to profiled sheets.


10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Krunoslav Vidovič
Technical director



Žarko Terčič, dipl. eng.
Director



Anhovo, 1. 7. 2013

