



## Fibro-Kustik *Florence*

WW acoustic board according to DIN EN 13168  
 WW WI dm / DI dm  
 Flame retardant (A2-s1, d0),  
 mineral bound  
 Super-fine wool (1mm thread width)

WW EN 13168-T2-L3-W2-P2-CI1-CS(10y)200

**Properties:**

- Wood-wool board, bound with cement
- Ecologically sound
- good sound absorption
- High vapor permeability
- Diffusion resistance factor 2/5
- General construction supervisory approval Z-23.15-1622



Promoting Sustainable  
Forest Management  
www.pefc.co.uk

**Color design**

- Nature
- for an extra charge:
- White sprayed as non-smear in RAL 9010
  - Other colours available when the RAL or NCS-no is provided

**Area of Application:**

Acoustic ceilings in residential and non-residential construction, e.g. commercial, industrial and public buildings, offices, schools, sports halls, and garages.

Article master	Board thickness in mm	Heat transfer resistance RD m <sup>2</sup> K/W	Standard in mm		Weight in kg		Contents per pallet (1200 x 1200mm) (1000 x 1200mm)	
			Length	Width	per m <sup>2</sup>	per pallet	Piece	m <sup>2</sup>
2590171015	15	0,20	1200/600	600	10,0	960	128	92,16
2590171025	25	0,33	1200/600	600	13,3	710	70	50,40
2590171025	25	0,33	1000/600	600	13,3	600	70	42,00



[www.blauer-engel.de/uz132](http://www.blauer-engel.de/uz132)

On request with the world-wide unique indoor air purifying effect:





# Fibrolith®

Natürlich Holzwolle

## Edge designs:


Direct mounting, inlay mounting, hidden mounting




**GKANTE**  
Straight edge




**FASE05**  
small beveled edge  
5mm




**FUGE05**  
straight edge with all-round  
rabbet for 5 mm wide joints  
(as of 25 mm)




**GK-EIN**  
Inlay assembly  
with straight edges




**SF-EIN**  
Inlay mounting  
with rabbet on visible side



**SF-EINF05**  
Inlay mounting  
with rabbet on visible side  
And all-round rabbet  
(as of 25 mm)



**VF05**  
Hidden edge  
cannot be removed  
(as of 25mm)



**VF05-DEM**  
Grooved along the length  
all-round beveled edge  
can be removed  
(as of 25 mm)

## Expert report

### Ball-proof wall cladding in accordance with DIN 18032/ Part 3

Product	Thickness in mm	Substructure	Attachment		Test certificate
			Axis distance	Screws	
<b>Fibro-Kustik Florence</b>	25	Wooden battens 80 x 30 mm	≤600mm	Acoustic screws in 45 mm lengths	903 1238 000/1/Man/H MPA Stuttgart
<b>Fibro-Kustik Florence</b>	25	CD profile 60 x 27 mm	≤600mm	6 pieces per pallet with 1200x600 mm format	903 1238 000/1/Man/H MPA Stuttgart

### Ball-proof ceiling cladding in accordance with DIN 18032/ Part 3

Product	Thickness in mm	Substructure	Attachment		Test certificate
			Axis distance	Screws	
<b>Fibro-Kustik Florence</b>	25	Wooden battens 80 x 30 mm	≤600mm	Acoustic screws in 45 mm lengths	903 1238 000/2/Man/H MPA Stuttgart
<b>Fibro-Kustik Florence</b>	25	CD profile 60 x 27 mm	≤600mm	6 pieces per pallet with 1200x600 mm format	903 1238 000/2/Man/H MPA Stuttgart

This technical information reflects the current level of our knowledge and experience. Subject to changes without prior notification. Please use the latest version of the product data sheet as levels of experience and knowledge are constantly developing. Please contact our office in the event of doubt. Examples of use described may not account for the specific circumstances of each individual case and we therefore accept no liability for them. Otherwise, only our General Terms of Sale, Delivery and Payment (latest version), of which you are aware, apply.

October 2019